

TECHNICAL SPECIFICATION

LoRa WAN Gateway

ALWG-1638



Features

- **LoRaWAN[®] Class A/B/C**
- **Multi-channel**
- **LTE and GSM with dual SIM support**
- **PoE Ethernet, GNSS and WiFi**
- **ARM Cortex-A7 quad core processor**
- **High gain LoRa antenna**
- **USB for debug**
- **SuperCAP backup**
- **Aluminium IP67 housing resistant to all weather conditions**

Multichannel LoRaWAN[®] Gateway, powered by ARM Cortex-A7 processor with an IP67 enclosure to handle tough environments. Standout features include an isolated power supply for protection and power

backup. The gateway's dual SIMs ensures network connectivity redundancy. Moreover, its multiple VPN support adds an extra layer of security, serving to diverse communication needs.

Description	Specification
Processor	
Type	ARM Cortex-A7
Number of cores	Quad core
Clock	960MHz per core
RAM Memory	
Memory size	512MB
Memory speed	1066MHz max
Storage	
Internal memory	8GB eMMC
USB	
USB port number	1
USB type	Device for debug, on bottom of the enclosure
Connector	C-type

Description	Specification
Protection	Surge protection
LoRaWAN[®]	
Compatibility	LoRaWAN, Class A/B/C
Frequency	IN865 (other country option available. Refer modem selection chart)
LoRa demodulators	8 x 8 channels LoRa packet detectors
	8x SF5-SF12 LoRa
	8x SF5-SF10 LoRa
	1x 125/250/500 kHz high-speed
Demodulation paths	Up to 10 parallel
Uplinks channel	8

Description	Specification
Downlink channel	1
TX power	Up to 27 dBm @ SF12, BW 125 kHz
RX sensitivity	Down to -139 dBm @ SF12, BW 125 kHz
Data-rate	Dynamic data-rate adaptation (ADR)
Module certification	USB-IN865 (other country option available. Refer selection chart)
Antenna connector	N-type
Ethernet	
Number	1
Type	1x 10/100M
PoE	PoE class A (38-58V DC)
WiFi	
Bands	2.4 GHz ISM
Standards	802.11 b/g/n, 802.3, 802.3u 802.11e-compatible bursting and I standards
Modulation schemes	BPSK, QPSK, 16 QAM, 64 QAM
Security	WEP, TKIP, and AES, WPA, WPA2
Antenna	Inbuilt inside the enclosure
Cellular Modem¹	
Cellular bands	Refer cellular specification chart
SIM card	Dual nanoSIM, tray type anti-loss holder 3V/1.8V
Antenna	Inbuilt inside the enclosure
GNSS	
GNSS systems	GPS, BDS, Galileo, GLONASS, QZSS
Antenna connector	Inbuilt inside the enclosure
Security	
VPN	Multiple VPN support
Login	User name and login access
Indicators	
Multifunction	1 RGB LED outside on bottom of the housing for all functions indication
Debug and Development	
System debug	C-type USB to UART inbuilt
Reset	Reset push button
Default	Default push button
Operating System	
OS	OpenWRT Linux
Forwarder	UDP forwarder ChirpStack MQTT forwarder
LNS	ChirpStack server

¹ Apply to LT models. Refer ordering and cellular specification chart.

Description	Specification
Other functions	Node-RED with ChirpStack support
Power Supply	
Power supply	PoE isolated EEE802.3af compliant 37-57V isolated
Power consumption	Up to 10W Average 5W (approx)
Connector	RJ45 (cable through gland)
Power backup	Inbuilt SuperCAP
Backup time	Approx 20s
Physical Characteristics	
Installation	Pole / wall mounting with attached stainless steel clamp.
Housing back	Aluminium alloy ADC-12 – Surtec 650, salt spray duration 96hrs
Housing front	Polycarbonate – UV stabilized, UL94 V0 rated, Sabic943(f1)
Cooling	Passive
Weight	920g (without antenna and clamp)
Dimensions	220×122×70mm (without antennas and cable gland)
Environmental Specification	
Operating temp.	-25 ~ 70°C (-13 ~ 158°F)
Storage temp.	40 ~ 85°C (-40 ~ 176°F)
Ambient RH	5% ~ 95% (non-condensing)
Protection class	IP67

Cellular modem specification of EU (Europe and India) version

EU version of gateway		Cellular network interface details	
Band LTE FTD	B1/3/5/7/8/20/28		
Band LTE TDD	B38/ 40/ 41		
Band GSM	B2/3/5/8 (900/1800MHz)		
GPRS slot	Multi-slot class 12/10		
Bandwidth	1.4/ 3/ 5/ 10/ 15/ 20 MHz		
Output power	LTE-FDD	Class 3 (23 dBm ±2 dB)	
	LTE-TDD	Class 3 (23 dBm ±2 dB)	
	EGSM900	Class 4 (33 dBm ±2 dB)	
	DCS1800	Class 1 (30 dBm ±2 dB)	
Maximum data rate	LTE-FDD	10 Mbps (DL)/ 5 Mbps (UL)	
	LTE-TDD	8.96 Mbps (DL)/ 3.1 Mbps (UL)	
	GSM	85.6 kbps (DL)/ 85.6 kbps (UL)	
Power	Compliant to GSM phase 2/2+		
	– Class 4 (2 W 900MHz)		
	– Class 1 (1 W 1800MHz)		

Cellular modem specification of GL (global) version

GL version of gateway	Cellular network interface details	
Band LTE FTD	B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28	
Band LTE TDD	B38/B39/B40/B41	
Band WCDMA	B1/B2/B4/B5/B6/B8/B19	
Band GSM	B2/B3/B5/B8	
Output power	GSM850	Class 4 (33 dBm ±2 dB)
	EGSM900	Class 4 (33 dBm ±2 dB)
	DCS1800	Class 1 (30 dBm ±2 dB)
	PCS1900	Class 1 (30 dBm ±2 dB)
	GSM850 8-PSK	Class E2 (27 dBm ±3 dB)
	EGSM900 8-PSK	Class E2 (27 dBm ±3 dB)
	DCS1800 8-PSK	Class E2 (26 dBm ±3 dB)
	PCS1900 8-PSK	Class E2 (26 dBm ±3 dB)
	WCDMA	Class 3 (24 dBm +1/-3 dB)
	LTE-FDD	Class 3 (23 dBm ±2 dB)
	LTE-TDD	Class 3 (23 dBm ±2 dB)
Maximum data rate LTE	LTE-FDD	150 Mbps (DL)/Max. 50 Mbps (UL)
	LTE-TDD	130 Mbps (DL)/Max. 30 Mbps (UL)
Maximum data rate UMTS	DC-HSDPA	42 Mbps (DL)
	HSUPA	5.76 Mbps (UL)
	WCDMA	384 kbps (DL)/Max. 384 kbps (UL)
Maximum data rate GSM	EDGE	296 kbps (DL)/Max. 236.8 kbps (UL)
	GPRS	107 kbps (DL)/Max. 85.6 kbps (UL)

Table with model structure for ordering

This table is applicable when ordering larger quantities of gateways and to optimize the selection of certain components.

Model Structure			
Model example		ALWG-1638- IN-LT- EU	
Base model name			
ALWG-1638			
LoRa frequency/country			
IN (IN865)			
US (US915) US, Canada, Mexico, Bolivia, Peru, Uruguay, Venezuela, Colombia, Ecuador, Panama, Paraguay			
EU (EU868) EU, Mauritius, Mozambique, Namibia, Saudi Arabia, South Africa, Turkey, UAE, UK, Finland, Madagascar, Malta, Switzerland, Tanzani			
AU (AU915) Australia, Brazil, Argentina, New Zealand, Chile			
AS (AS923) Hong-Kong, Singapore, Taiwan, Vietnam, Cambodia, Japan, Malaysia			
RU (RU864) Russia			
Cellular modem			
LT (cellular modem present)			
Cellular regional information			
EU (cellular modem for India and Europe)			
GL (global cellular modem)			

**For more details
scan or click on
QR code**



Copyright

Copyright © 2024 Atreyo Research and Development LLP. This technical specification is protected under national and international copyright laws. No part of this user manual may be reproduced, distributed, translated, or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording, or storing in any information storage and retrieval system, without the prior written permission of Atreyo Research and Development LLP. Copy or use any part of this specifications is prohibited without the prior written permission from the Atreyo Research and Development LLP.

Trademarks

Atreyo and the Atreyo logo are registered trademarks of Atreyo Research and Development LLP.

All other trademarks and copyrights are the property of their respective owners.

Disclaimer

- The information contained in this datasheet is provided "as is" and is subject to change without notice. While every effort has been made to ensure the accuracy and completeness of the information contained herein, Atreyo Research and Development LLP assumes no responsibility or liability for any errors or omissions.
- Images used in this specification may differ in appearance from the actual product.
- All dimensions mentioned in the drawings are not to scale and are subject to change and update as may be decided by the Atreyo Research and Development LLP.
- Atreyo Research and Development LLP makes no warranties, either express or implied, regarding the contents of this document, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.
- Users of this datasheet should verify the applicability and suitability of the information and procedures to their particular use. Atreyo Research and Development LLP shall not be liable for any damages, including but not limited to direct, indirect, special, incidental, or consequential damages, arising from or related to the use or inability to use this datasheet or the products described herein.
- By using this datasheet, you agree to the terms and conditions stated above. Atreyo Research and Development LLP shall not be liable for any damages, including but not limited to direct, indirect, special, incidental, or consequential damages, arising from or related to the use or inability to use this datasheet or the products described herein.

**Atreyo Research
& Development LLP**

**+91 9727741417
info@atreyo.in**

414, Sunrise Mall, Mansi Circle,
Ahmedabad, Gujarat, India