

High Voltage 8 Input Extender with Modbus

AMB-8I



Features

- 8 × 60-500V DC/AC digital inputs
- Baud rate: 9600 – 128000
- Modbus addresses: 8 bit
- RX/TX and activity indicators
- Powered 8-36V DC or 8-24VAC
- DIN rail mounting

Digital input extender with high voltage range from 60V AC up to 500V AC to Modbus RTU. Input also support DC voltage

in same voltage range. The power supply range is 8 to 36V and accept DC or AC voltage.

Description	Parameter
Serial Interface	
Interface Type	RS485
Data Rate	9600bps ~ 128000bps
Signals	A, B and GND
Data Length	8 bits
Parity	None
Stop Bits	1
Baudrate setting	4 way DIP switch
Address setting	8 way DIP switch
Connector	Screw connector, 28÷12AWG / 2.52mm
Digital Inputs	
Input number	×8
Input type	Opto-isolated Opto-isolated 1kV
Configuration	Every input separate
VIN _{max}	500V AC or 500V DC
Logic 1 Voltage range	60V to VIN _{max}
Connector	Screw connector, 28÷12AWG / 2.52mm

Description	Parameter
Indicators	
Inputs indicators	× 8 3mm LED green
RX/TX	× 2 3mm LED yellow/green
Power	× 1 3mm LED red
Activity	× 1 3mm LED blue
Power supply	
Supply voltage	8-36V DC or 8-24AC
Power consumption	
Connector type	Screw connector, 28÷12AWG / 2.52mm
Physical Characteristics	
Installation	DIN-Rail mounting
Housing	PVC
Dimensions (L×W×H)	80mm × 90mm × 50mm
Weight	100g
Environmental Specification	
Operating Temp.	-25 ~ 70°C (-13 ~ 158°F)
Storage Temp.	-40 ~ 85°C (-40 ~ 176°F)
Ambient RH	5% to 95% (non-condensing)

Model selection chart

Sn.	Model	Description
1	AMB-8I	Default specification
2	AMB-8I-DC	With low voltage inputs 30V AC/DC

Copyright

Copyright © 2022 Atreyo Research and Development LLP. This technical specification is protected under national and international copyright laws. No part of this user manual may be reproduced, distributed, translated, or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording, or storing in any information storage and retrieval system, without the prior written permission of Atreyo Research and Development LLP. Copy or use any part of this specifications is prohibited without the prior written permission from the Atreyo Research and Development LLP. Atreyo Research and Development LLP shall not unreasonably withhold or deny such consent but shall be entitled to receive additional equitable remuneration in connection with its grant of consent.

Trademarks

Atreyo and the Atreyo logo are registered trademarks of Atreyo Research and Development LLP.

All other trademarks and copyrights are the property of their respective owners.

Disclaimer

- All dimensions mentioned in the drawings are not to scale and may vary/differ due to construction contingencies and site conditions which are subject to change as may be decided by the company.
- The specifications and amenities mentioned in this document and promotional documents are only representational and informative. The descriptions in this specification are based on the default configuration of your device.
- Images used in this specification may differ in appearance from the actual product.
- The Atreyo Research and Development LLP reserves rights to make additions, deletions, alterations or amendments as and when it deems fit and proper, without any prior notice.

**Atreyo Research
& Development LLP**

**+91 9727741417
info@atreyo.in**

414, Sunrise Mall, Mansi Circle,
Vastrapur
Ahmedabad 380015, India