


TECHNICAL SPECIFICATION

8 input 4 output expander with
Modbus and IEC-60870-5-101

AMB-8I-4O



Features

- 8 × 5-30V DC isolated digital input
- 4 × NO relay outputs 7A
- Modbus RTU
- IEC-60870-5-101¹
- Baud rate: 1200 – 921600
- Modbus addresses: 8 bit
- RX/TX and activity indicators
- Save config button
- Powered 8-48V DC
- DIN rail mounting
- Compact size

The AMB-8I-4O input/output expander with Modbus RTU and IEC-60870-5-101 protocol support (under development). It has 8 isolated digital inputs with voltage range up to 30VDC and 4 relay output with 7A

230V range and NO contacts. The power supply range is 8 to 48V DC. The use of DC / DC technology for supplying relays enables a wide range of supply voltages.

Description	Specification
Serial interface	
Interface Type	RS485
Signals	A, B and GND
Data Length	8 bits
Parity	None, odd, even
Stop Bits	1
Setting	12 way DIP switch
Connector	Screw connector, 28÷12AWG / 2.52mm
Digital inputs	
Input number	× 8
Input type	Opto-isolated 2.5kV


Description	Specification
Configuration	Every input separate
VIN _{max}	30V DC
Logic 1 Voltage range	3V to VIN _{max}
Connector	Screw connector, 28÷12AWG / 2.52mm
Digital outputs	
Output number	× 4
Configuration	Potential free, relay NO
Voltage and Load	7A 230V AC and 7A 30V DC
Connector type	Screw connector, 28÷12AWG / 2.52mm

¹ please refer the functionality of IEC-60870-5-101 in [online documentation](#)

Description	Specification
Modbus RTU	
Data Rate	1200, 2400, 4800, 9600, 14400, 19200, 28800, 38400, 57600, 115200, 230400, 256000, 560800, 576000, 921600 bps
Address	1 to 10 and 10 to 247
IEC-60870-5-101	
Data Rate	1200, 2400, 4800, 9600, 14400, 19200, 28800, 38400, 57600, 115200, 230400, 256000, 560800, 576000, 921600 bps
Address	1 to 10 and 10-90
Link mode	Balanced/unbalanced
System functions indicators	
Inputs indicators	× 8 ø3mm LED green
Outputs indicators	× 4 ø3mm LED red
RX/TX	× 2 ø3mm LED yellow/green
Power	× 1 ø3mm LED red

Description	Specification
Activity	× 1 ø3mm LED blue
Power supply	
Voltage range	8-48V DC
Consumption	0.2W without relay on
Connector	Screw connector, 28÷12AWG / 2.52mm
Protection	Reverse polarity, surge
Physical characteristics	
Installation	DIN-Rail mounting
Housing	PVC
Weight	125g
Dimensions	100mm x 90mm x 50mm
Environmental specification	
Operating Temp.	-25 ~ 85°C (-13 ~ 158°F)
Storage Temp.	-40 ~ 85°C (-40 ~ 176°F)
Ambient RH	5% to 95% (non-condensing)

Interface



**For more details
scan or click on
QR code**



Copyright

Copyright © 2025 Atreyo Research and Development LLP. This technical specification is protected under national and international copyright laws. No part of this user manual may be reproduced, distributed, translated, or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording, or storing in any information storage and retrieval system, without the prior written permission of Atreyo Research and Development LLP. Copy or use any part of this specifications is prohibited without the prior written permission from the Atreyo Research and Development LLP.

Trademarks

Atreyo and the Atreyo logo are registered trademarks of Atreyo Research and Development LLP. All other trademarks and copyrights are the property of their respective owners.

Disclaimer

- The information contained in this datasheet is provided "as is" and is subject to change without notice. While every effort has

been made to ensure the accuracy and completeness of the information contained herein, Atreyo Research and Development LLP assumes no responsibility or liability for any errors or omissions.

- Images used in this specification may differ in appearance from the actual product.
- All dimensions mentioned in the drawings are not to scale and are subject to change and update as may be decided by the Atreyo Research and Development LLP.
- Atreyo Research and Development LLP makes no warranties, either express or implied, regarding the contents of this document, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.
- Users of this datasheet should verify the applicability and suitability of the information and procedures to their particular use. Atreyo Research and Development LLP shall not be liable for any damages, including but not limited to direct, indirect, special, incidental, or consequential damages, arising from or related to the use or inability to use this datasheet or the products described herein.
- By using this datasheet, you agree to the terms and conditions stated above.

**Atreyo Research
& Development LLP**

**+91 9727741417
info@atreyo.in**

414, Sunrise Mall, Mansi Circle,
Ahmedabad, Gujarat, India